

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

| | |
|----------------------------------|--|
| Product Description: | <u>Dichloromethane</u> |
| Cat No. : | D/1852/08, D/1852/15, D/1852/17, D/1852/17X, D/1852/21, D/1852/24, D/1852/25, D/1852/27, D/1852/27SS, D/1852/DH25, D/1852/PB15, D/1852/PB15X, D/1852/PB17, D/1852/21RSS, D/1852/24RSS, D/1852/25RSS, D/1852/34RSS, D/1852/27RSS, D/1852/PC15, D/1852/10RSS |
| Synonyms | Dichloromethane; DCM |
| Index No | 602-004-00-3 |
| CAS No | 75-09-2 |
| EC No | 200-838-9 |
| Molecular Formula | C H ₂ Cl ₂ |
| REACH registration number | 01-2119480404-41 |

1.2. Relevant identified uses of the substance or mixture and uses advised against

| | |
|---------------------------------------|--|
| Recommended Use | Laboratory chemicals. |
| Sector of use | SU3 - Industrial uses: Uses of substances as such or in preparations at industrial sites SU5 - Manufacture of textiles, leather, fur SU8 - Manufacture of bulk, large scale chemicals (including petroleum products) SU9 - Manufacture of fine chemicals SU10 - Formulation [mixing] of preparations and/or re-packaging (excluding alloys) SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen) SU24 - Scientific research and development |
| Product category | PC21 - Laboratory chemicals |
| Process categories | PROC15 - Use as a laboratory reagent see SECTION 16 for a complete list of uses for which an exposure scenario is provided as an annex |
| Environmental release category | ERC1 - Manufacture of substances ERC2 - Formulation of preparations ERC4 - Industrial use of processing aids in processes and products, not becoming part of articles ERC8a - Wide dispersive indoor use of processing aids in open systems |
| Uses advised against | SU21 - Consumer uses: Private households (= general public = consumers) REACH Annex XVII Restriction - refer to SECTION 15 |

1.3. Details of the supplier of the safety data sheet

| | |
|-----------------------|--|
| Company | UK entity/business name Fisher Scientific UK Bishop Meadow Road, Loughborough, Leicestershire LE11 5RG, United Kingdom |
| | EU entity/business name Thermo Fisher Scientific Janssen Pharmaceuticaaan 3a 2440 Geel, Belgium |
| E-mail address | begel.sdsdesk@thermofisher.com |

SAFETY DATA SHEET

Dichloromethane

Revision Date 23-Oct-2023

1.4. Emergency telephone number

Tel: 01509 231166
Chemtrec US: (800) 424-9300
Chemtrec EU: 001-703-527-3887

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

CLP Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

Physical hazards

Based on available data, the classification criteria are not met

Health hazards

| | |
|--|-------------------|
| Skin Corrosion/Irritation | Category 2 (H315) |
| Serious Eye Damage/Eye Irritation | Category 2 (H319) |
| Carcinogenicity | Category 2 (H351) |
| Specific target organ toxicity - (single exposure) | Category 3 (H336) |

Environmental hazards

Based on available data, the classification criteria are not met

Full text of Hazard Statements: see section 16

2.2. Label elements



Signal Word

Warning

Hazard Statements

H315 - Causes skin irritation
H319 - Causes serious eye irritation
H336 - May cause drowsiness or dizziness
H351 - Suspected of causing cancer

Precautionary Statements

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water
P337 + P313 - If eye irritation persists: Get medical advice/attention
P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
P312 - Call a POISON CENTER or doctor if you feel unwell
P280 - Wear protective gloves/protective clothing/eye protection/face protection

SAFETY DATA SHEET

Dichloromethane

Revision Date 23-Oct-2023

2.3. Other hazards

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB)
Causes formation of carbon monoxide in the blood. Carbon monoxide may cause adverse effects on the cardiovascular system and the central nervous system
Toxic to terrestrial vertebrates
This product does not contain any known or suspected endocrine disruptors

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

| Component | CAS No | EC No | Weight % | CLP Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567 |
|--------------------|---------|-------------------|----------|---|
| Methylene chloride | 75-09-2 | EEC No. 200-838-9 | >99.5 | Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) STOT SE 3 (H336) Carc. 2 (H351) |

Note

Stabilised with Amylene (CAS 513-35-9)

| | |
|---------------------------|------------------|
| REACH registration number | 01-2119480404-41 |
|---------------------------|------------------|

Full text of Hazard Statements: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

| | |
|---|---|
| General Advice | If symptoms persist, call a physician. |
| Eye Contact | Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention. |
| Skin Contact | Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician. |
| Ingestion | Clean mouth with water and drink afterwards plenty of water. |
| Inhalation | Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms occur. |
| Self-Protection of the First Aider | Use personal protective equipment as required. |

4.2. Most important symptoms and effects, both acute and delayed

. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting: Causes central nervous system depression: Continued or high exposures by inhalation will cause anaesthetic effects. This may result in a loss of consciousness and could prove fatal: Causes formation of carbon monoxide in the blood. Carbon monoxide may cause adverse effects on the cardiovascular system and the central nervous system

SAFETY DATA SHEET

Dichloromethane

Revision Date 23-Oct-2023

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically. Symptoms may be delayed.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

Water spray, carbon dioxide (CO₂), dry chemical, alcohol-resistant foam.

Extinguishing media which must not be used for safety reasons

No information available.

5.2. Special hazards arising from the substance or mixture

Thermal decomposition can lead to release of irritating gases and vapors. Keep product and empty container away from heat and sources of ignition.

Hazardous Combustion Products

Carbon monoxide (CO), Carbon dioxide (CO₂), Phosgene, Hydrogen chloride gas.

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment as required. Ensure adequate ventilation. Avoid breathing vapors or mists. Wear respiratory protection.

6.2. Environmental precautions

Should not be released into the environment.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Vapors are heavier than air and may spread along floors. Handle product only in closed system or provide appropriate exhaust ventilation. Reacts with aluminum and its alloys.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice.

SAFETY DATA SHEET

Dichloromethane

Revision Date 23-Oct-2023

7.2. Conditions for safe storage, including any incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Do not store in aluminum containers.

Technical Rules for Hazardous Substances (TRGS) 510 Class 6.1D
Storage Class (LGK) (Germany)

7.3. Specific end use(s)

Use in laboratories

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limits

List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Fourth edition. Published 2020. **IRE** - 2021 Code of Practice for the Chemical Agents Regulations, Schedule 1. Published by the Health and Safety Authority

| Component | The United Kingdom | European Union | Ireland |
|--------------------|--|--|--|
| Methylene chloride | STEL: 200 ppm 15 min STEL: 706 mg/m ³ 15 min TWA: 353 mg/m ³ 8 hr TWA: 100 ppm 8 hr Skin | TWA: 353 mg/m ³ (15min) TWA: 100 ppm (15min) STEL: 706 mg/m ³ (8h) STEL: 200 ppm (8h) Skin | TWA: 100 ppm 8 hr. TWA: 353 mg/m ³ 8 hr. STEL: 200 ppm 15 min STEL: 706 mg/m ³ 15 min Skin |

Biological limit values

List source(s): **UK** - Biological Monitoring Guidance Values provided by the UK's Health and Safety Executive (HSE) Control of Substances Hazardous to Health Regulations (COSHH) 2002 (as amended) and EH40/2005.

| Component | United Kingdom | European Union |
|--------------------|---|----------------|
| Methylene chloride | Carbon monoxide: 30 ppm end-tidal breath post shift | |

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

| Component | Acute effects local (Dermal) | Acute effects systemic (Dermal) | Chronic effects local (Dermal) | Chronic effects systemic (Dermal) |
|---------------------------------------|------------------------------|---------------------------------|--------------------------------|-----------------------------------|
| Methylene chloride 75-09-2 (>99.5) | | | | DNEL = 12mg/kg bw/day |

| Component | Acute effects local (Inhalation) | Acute effects systemic (Inhalation) | Chronic effects local (Inhalation) | Chronic effects systemic (Inhalation) |
|---------------------------------------|----------------------------------|-------------------------------------|------------------------------------|---------------------------------------|
| Methylene chloride 75-09-2 (>99.5) | | DMEL = 132.14mg/m ³ | | DNEL = 176mg/m ³ |

Predicted No Effect Concentration (PNEC)

Predicted No Effect Concentration (PNEC). See values below.

| Component | Fresh water | Fresh water sediment | Water Intermittent | Microorganisms in sewage treatment | Soil (Agriculture) |
|---------------------------------------|-----------------------------------|---|--------------------|------------------------------------|---|
| Methylene chloride 75-09-2 (>99.5) | PNEC = 130µg/L PNEC = 0.31mg/L | PNEC = 163µg/kg sediment dw PNEC = 2.57mg/kg sediment dw | PNEC = 0.27mg/L | PNEC = 26mg/L | PNEC = 173µg/kg soil dw PNEC = 0.33mg/kg soil dw |

SAFETY DATA SHEET

Dichloromethane

Revision Date 23-Oct-2023

| Component | Marine water | Marine water sediment | Marine water intermittent | Food chain | Air |
|---|------------------------------------|---|---------------------------|------------|-----|
| Methylene chloride 75-09-2 (>99.5) | PNEC = 130µg/L PNEC = 0.031mg/L | PNEC = 163µg/kg sediment dw PNEC = 0.26mg/kg sediment dw | PNEC = 0.027mg/L | | |

8.2. Exposure controls

Engineering Measures

Use only under a chemical fume hood. Ensure that eyewash stations and safety showers are close to the workstation location. Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection Goggles (European standard - EN 166)

Hand Protection Protective gloves

| Glove material | Breakthrough time | Glove thickness | EU standard | Glove comments |
|----------------|-----------------------------------|-----------------|-------------|-----------------------|
| Viton (R) | See manufacturers recommendations | - | EN 374 | (minimum requirement) |

Skin and body protection Long sleeved clothing.

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Respiratory Protection When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

Large scale/emergency use Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced
Recommended Filter type: low boiling organic solvent Type AX Brown conforming to EN371

Small scale/Laboratory use Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.
Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN 141
When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls No information available.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical State Liquid

Appearance Colorless

SAFETY DATA SHEET

Dichloromethane

Revision Date 23-Oct-2023

| | | |
|--|--|--|
| Odor | sweet | |
| Odor Threshold | No data available | |
| Melting Point/Range | -97 °C / -142.6 °F | |
| Softening Point | No data available | |
| Boiling Point/Range | 39 °C / 102.2 °F | |
| Flammability (liquid) | No data available | |
| Flammability (solid,gas) | Not applicable | Liquid |
| Explosion Limits | Lower 13 vol% Upper 22 vol% | |
| Flash Point | No information available | Method - No information available |
| Autoignition Temperature | 556 - °C / 1032.8 - °F | |
| Decomposition Temperature | No data available | |
| pH | No information available | |
| Viscosity | 0.42 mPas @ 25°C | |
| Water Solubility | 20 g/L (20°C) | |
| Solubility in other solvents | No information available | |
| Partition Coefficient (n-octanol/water) | | |
| Component | log Pow | |
| Methylene chloride | 1.25 | |
| Vapor Pressure | 350 mbar @ 20°C | |
| Density / Specific Gravity | 1.33 | |
| Bulk Density | Not applicable | Liquid |
| Vapor Density | 2.93 (Air = 1.0) | (Air = 1.0) |
| Particle characteristics | Not applicable (liquid) | |

9.2. Other information

| | |
|--------------------------|----------|
| Molecular Formula | C H2 Cl2 |
| Molecular Weight | 84.93 |

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

None known, based on information available

10.2. Chemical stability

Stable under normal conditions. Decomposes on exposure to light.

10.3. Possibility of hazardous reactions

| | |
|---------------------------------|---|
| Hazardous Polymerization | Hazardous polymerization does not occur. |
| Hazardous Reactions | Forms a detonable mixture with nitric acid. |

10.4. Conditions to avoid

Excess heat. Protect from direct sunlight.

10.5. Incompatible materials

Strong oxidizing agents. Strong acids. Amines.

10.6. Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO₂). Phosgene. Hydrogen chloride gas.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

SAFETY DATA SHEET

Dichloromethane

Revision Date 23-Oct-2023

Product Information

- (a) acute toxicity;
- Oral Based on available data, the classification criteria are not met
 - Dermal Based on available data, the classification criteria are not met
 - Inhalation Based on available data, the classification criteria are not met

| Component | LD50 Oral | LD50 Dermal | LC50 Inhalation |
|--------------------|----------------------|----------------------|--|
| Methylene chloride | > 2000 mg/kg (Rat) | > 2000 mg/kg (Rat) | 53 mg/L (Rat) 6 h 76000 mg/m ³ (Rat) 4 h |

- (b) skin corrosion/irritation; Category 2

- (c) serious eye damage/irritation; Category 2

- (d) respiratory or skin sensitization;
- Respiratory Based on available data, the classification criteria are not met
 - Skin Based on available data, the classification criteria are not met

- (e) germ cell mutagenicity; Based on available data, the classification criteria are not met
Mutagenic effects have occurred in microorganisms

- (f) carcinogenicity; Category 2
The table below indicates whether each agency has listed any ingredient as a carcinogen

| Component | EU | UK | Germany | IARC |
|--------------------|----|----|---------|----------|
| Methylene chloride | | | | Group 2A |

- (g) reproductive toxicity; Based on available data, the classification criteria are not met

- (h) STOT-single exposure; Category 3
Results / Target organs Central nervous system (CNS).

- (i) STOT-repeated exposure; Based on available data, the classification criteria are not met
Target Organs None known.

- (j) aspiration hazard; Based on available data, the classification criteria are not met

Other Adverse Effects Tumorigenic effects have been reported in experimental animals.

Symptoms / effects, both acute and delayed Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Causes central nervous system depression. Continued or high exposures by inhalation will cause anaesthetic effects. This may result in a loss of consciousness and could prove fatal. Causes formation of carbon monoxide in the blood. Carbon monoxide may cause adverse effects on the cardiovascular system and the central nervous system.

11.2. Information on other hazards

Endocrine Disrupting Properties Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

SAFETY DATA SHEET

Dichloromethane

Revision Date 23-Oct-2023

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity effects

| Component | Freshwater Fish | Water Flea | Freshwater Algae |
|--------------------|--|--------------------|--------------------|
| Methylene chloride | Pimephales promelas: LC50:193 mg/L/96h | EC50: 140 mg/L/48h | EC50:>660 mg/L/96h |

| Component | Microtox | M-Factor |
|--------------------|---|----------|
| Methylene chloride | EC50: 1 mg/L/24 h EC50: 2.88 mg/L/15 min | |

12.2. Persistence and degradability

Persistence

Persistence is unlikely, based on information available.

12.3. Bioaccumulative potential

Bioaccumulation is unlikely

| Component | log Pow | Bioconcentration factor (BCF) |
|--------------------|---------|-------------------------------|
| Methylene chloride | 1.25 | 6.4 - 40 dimensionless |

12.4. Mobility in soil

The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces. Will likely be mobile in the environment due to its volatility. Disperses rapidly in air.

12.5. Results of PBT and vPvB assessment

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB).

12.6. Endocrine disrupting properties

Endocrine Disruptor Information

This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects Persistent Organic Pollutant Ozone Depletion Potential

This product does not contain any known or suspected substance
This product does not contain any known or suspected substance

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues/Unused Products

Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated Packaging

Dispose of this container to hazardous or special waste collection point.

European Waste Catalogue (EWC)

According to the European Waste Catalog, Waste Codes are not product specific, but application specific.

Other Information

Waste codes should be assigned by the user based on the application for which the product was used. Do not empty into drains.

SAFETY DATA SHEET

Dichloromethane

Revision Date 23-Oct-2023

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

14.1. UN number UN1593
14.2. UN proper shipping name Dichloromethane
14.3. Transport hazard class(es) 6.1
14.4. Packing group III

ADR

14.1. UN number UN1593
14.2. UN proper shipping name Dichloromethane
14.3. Transport hazard class(es) 6.1
14.4. Packing group III

IATA

14.1. UN number UN1593
14.2. UN proper shipping name Dichloromethane
14.3. Transport hazard class(es) 6.1
14.4. Packing group III

14.5. Environmental hazards No hazards identified
14.6. Special precautions for user No special precautions required.
14.7. Maritime transport in bulk according to IMO instruments Not applicable, packaged goods

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

| Component | CAS No | EINECS | ELINCS | NLP | IECSC | TCSI | KECL | ENCS | ISHL |
|--------------------|---------|-----------|--------|-----|-------|------|----------|------|------|
| Methylene chloride | 75-09-2 | 200-838-9 | - | - | X | X | KE-23893 | X | X |

| Component | CAS No | TSCA | TSCA Inventory notification - Active-Inactive | DSL | NDSL | AICS | NZIoC | PICCS |
|--------------------|---------|------|---|-----|------|------|-------|-------|
| Methylene chloride | 75-09-2 | X | ACTIVE | X | - | X | X | X |

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

Authorisation/Restrictions according to EU REACH

| Component | CAS No | REACH (1907/2006) - Annex XIV - Substances Subject to Authorization | REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances | REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC) |
|--------------------|---------|---|---|---|
| Methylene chloride | 75-09-2 | - | Use restricted. See item 59. | - |

SAFETY DATA SHEET

Dichloromethane

Revision Date 23-Oct-2023

| | | | |
|--|--|--|--|
| | | | (see link for restriction details) Use restricted. See item 75. (see link for restriction details) |
|--|--|--|--|

REACH links

<https://echa.europa.eu/substances-restricted-under-reach>

Seveso III Directive (2012/18/EC)

| Component | CAS No | Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification | Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements |
|--------------------|---------|---|--|
| Methylene chloride | 75-09-2 | Not applicable | Not applicable |

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification

See table for values

| Component | Germany - Water Classification (AwSV) | Germany - TA-Luft Class |
|--------------------|---------------------------------------|--|
| Methylene chloride | WGK2 | Class I : 20 mg/m ³ (Massenkonzentration) |

| Component | France - INRS (Tables of occupational diseases) |
|--------------------|--|
| Methylene chloride | Tableaux des maladies professionnelles (TMP) - RG 12 |

| Component | Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81) | Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC) | Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure |
|---|--|---|---|
| Methylene chloride 75-09-2 (>99.5) | Persistent Organic Pollutants (POPs) Prohibited and Restricted Substances | Group I | |

15.2. Chemical safety assessment

A Chemical Safety Assessment/Report (CSA/CSR) has been conducted

SAFETY DATA SHEET

Dichloromethane

Revision Date 23-Oct-2023

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H315 - Causes skin irritation
H319 - Causes serious eye irritation
H336 - May cause drowsiness or dizziness
H351 - Suspected of causing cancer

Legend

CAS - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration

PBT - Persistent, Bioaccumulative, Toxic

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer Predicted No Effect Concentration (PNEC)

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - (Volatile Organic Compound)

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Chemical incident response training.

Creation Date 27-Jan-2010

Revision Date 23-Oct-2023

Revision Summary Not applicable.

This safety data sheet complies with Regulation UK SI 2019/758 and UK SI 2020/1577 as amended.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet

Annex to the Safety Data Sheet according to Regulation (EC) No 1907/2006 [REACH]

Dichloromethane - Exposure Scenarios

| | | |
|--------------------------|---|---------------------------|
| CAS No 75-09-2 | REACH registration number 01-2119480404-41-xxxx | EC No 200-838-9 |
|--------------------------|---|---------------------------|

| Exposure Scenarios Overview | | | | |
|--|---|------------------------|---|---------------|
| Title | Sector of use | Process category(ies) | Environmental release category | ES Identifier |
| Manufacture, Recycling and Distribution (Industrial) | SU3 - Industrial uses: Uses of substances as such or in preparations at industrial sites SU8 - Manufacture of bulk, large scale chemicals (including petroleum products) SU9 - Manufacture of fine chemicals | 1, 2, 3, 4, 8a, 8b, 9 | ERC1 - Manufacture of substances | ES1-M1 DCM |
| Use as a process solvent / extraction medium | SU3 - Industrial uses: Uses of substances as such or in preparations at industrial sites SU5 - Manufacture of textiles, leather, fur SU9 - Manufacture of fine chemicals | 1, 2, 3, 4, 10, 15 | ERC4 - Industrial use of processing aids in processes and products, not becoming part of articles | ES2-M2 DCM |
| Formulation of preparations and/or re-packaging | SU3 - Industrial uses: Uses of substances as such or in preparations at industrial sites SU10 - Formulation [mixing] of preparations and/or re-packaging (excluding alloys) | 3, 4, 5, 8a, 8b, 9, 15 | ERC2 - Formulation of preparations | ES4-F1 DCM |
| Laboratory use | SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen) SU24 - Scientific research and development | 10, 15 | ERC8a - Wide dispersive indoor use of processing aids in open systems | ES5-L1 DCM |

Exposure scenario

Methylene chloride - ES1-M1 DCM

Section 1 - Identification of the use

| | |
|---|---|
| Main user group | Industrial use |
| Type | Worker |
| Processes, tasks, activities covered | Manufacture; Includes recycling / recovery; Loading (including marine vessel/barge, rail/road car and IBC loading) and repacking (including drums and small packs) of substance, including its sampling, storage, unloading distribution and associated laboratory activities |
| Sector(s) of use | SU3 - Industrial uses: Uses of substances as such or in preparations at industrial sites |

| | |
|------------------------------|--|
| | SU8 - Manufacture of bulk, large scale chemicals (including petroleum products) SU9 - Manufacture of fine chemicals |
| Process category(ies) | PROC1 - Use in closed process, no likelihood of exposure PROC2 - Use in closed, continuous process with occasional controlled exposure PROC3 - Use in closed batch process (synthesis or formulation) PROC4 - Use in batch and other process (synthesis) where opportunity for exposure arises PROC8a - Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non dedicated facilities PROC8b - Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities PROC9 - Transfer of substance or preparation into small containers (dedicated filling line, including weighing) PROC15 - Use as laboratory reagent |

Environmental release category(ies) ERC1 - Manufacture of substances

Section 2 - Operational Conditions and Risk Management Measures

Product characteristics

| | |
|-----------------------------------|--------------------------------------|
| Physical State | Liquid |
| pH | No information available |
| Water Solubility | Partially miscible; 13.2 g/L @ 25 °C |
| Vapor Pressure | 325 mmHg @ 20°C |
| Volatility | High |
| Covers concentrations up to 100 % | |

Section 2.1 - Control of environmental exposure

Environmental release category(ies)

ERC1 - Manufacture of substances

Control of environmental exposure

Readily biodegradable
Annual amount used in the EU 103000 t/a
Annual amount per site 25700 t/a

Environmental factors not influenced by risk management

| | |
|--|------------|
| Emission days | 300 |
| Receiving water dilution (fresh or marine) | 18000 m3/d |

Other operational conditions of use affecting environmental exposure

| | |
|--|-------------------------------|
| Emission days | 300 (from ESVOC SPERC 1.1.v1) |
| Release fraction to air from process (initial release prior to RMM) | 0.0000596 |
| Release fraction to wastewater from process (initial release prior to RMM) | 0.0000369 |
| Release fraction to soil from process (initial release prior to RMM) | 0.0 |

Technical onsite conditions and measures to reduce or limit discharges, air emissions

Technical onsite conditions and measures to reduce or limit discharges, air emissions
Negligible air emissions as process operates in a contained system.
Additional good practice advice beyond the REACH Chemical Safety Report
Bund storage facilities to prevent soil and water pollution in the event of spillage. Ensure all waste water is collected and treated via a WWTP.

Conditions and measures related to municipal sewage treatment plant

Remarks Manufacturing plants will have on-site waste water treatment facilities and emission to the municipal STP will not occur.

Waste management

| | |
|-------|--|
| Air | No discharge. No air emission controls required. |
| Water | Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of 93.5% |

Conditions and measures related to external treatment of waste for disposal

| | |
|-------------------------|---|
| Disposal | Waste resulting from on-site RMM to be disposed as chemical waste |
| Waste treatment methods | Hazardous waste incineration |

Section 2.2 - Control of worker exposure**General information on risk management related to physicochemical hazard**

Keep equipment under negative pressure. Segregate work area and mark with appropriate signs in accordance with local/regional/national legislation.

General information on exposure estimation

Manufactured and processed at industrial sites in closed continuous processes with either no likelihood of exposure or with only occasional opportunity for exposure in controlled conditions e.g. during maintenance, sampling or discharge of the material. Transfer of the substance is conducted at dedicated facilities using a closed-system with vapour return. Respiratory protection is not required except for certain critical activities where respiratory protective equipment is used, for example, cleaning tanks or reactors. Measured dermal exposure data are not available.

Control of worker exposure

| | |
|--|---|
| Process category(ies) | PROC1 - Use in closed process, no likelihood of exposure |
| Covers concentrations up to | 100% |
| Amounts used | >1000 t/y |
| Exposure duration | < 8h hour(s) |
| Use frequency | 220 days per year |
| Indoor/Outdoor use | Indoor |
| Assumes process temperature up to | <=40°C |
| Organisational measures to prevent /limit releases, dispersion and exposure | Handle substance within a closed system Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimize exposures and to report any skin problems that may develop |
| Technical conditions and measures to control dispersion from source towards the worker | Undertake operation under enclosed conditions |
| Conditions and measures related to personal protection, hygiene and health evaluation | Use eye protection according to EN 166, designed to protect against liquid splashes Wear chemically resistant gloves (tested to EN374) in combination with specific activity training |
| Additional good practice advice beyond the REACH Chemical Safety Report | Workers involved in production, handling, sampling and transfer of materials are well-trained in these procedures as well as good industrial hygiene practices ----- |
| Process category(ies) | PROC2 - Use in closed, continuous process with occasional controlled exposure |
| Covers concentrations up to | 100% |
| Exposure duration | < 8h hour(s) |
| Indoor/Outdoor use | Indoor |
| Assumes process temperature up to | <=40°C |
| Organisational measures to prevent /limit releases, dispersion and exposure | Handle substance within a closed system Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimize exposures and to report any skin problems that may develop |
| Conditions and measures related to personal protection, hygiene and health evaluation | Wear a respirator providing a minimum efficiency of 90% (APF 10) Use eye protection according to EN 166, designed to protect against liquid splashes Wear chemically resistant gloves (tested to EN374) in combination with specific activity training |
| Additional good practice advice beyond the REACH Chemical Safety Report | Workers involved in production, handling, sampling and transfer of materials are well-trained in these procedures as well as good industrial hygiene practices ----- |
| Process category(ies) | PROC3 - Use in closed batch process (synthesis or formulation) |
| Covers concentrations up to | 100% |
| Exposure duration | < 8 hour(s) |
| Indoor/Outdoor use | Indoor |
| Assumes process temperature up to | <=40°C |
| Organisational measures to prevent | Handle substance within a predominantly closed system provided with extract ventilation |

| | |
|---|---|
| /limit releases, dispersion and exposure | Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimize exposures and to report any skin problems that may develop |
| Conditions and measures related to personal protection, hygiene and health evaluation | Use eye protection according to EN 166, designed to protect against liquid splashes Wear chemically resistant gloves (tested to EN374) in combination with specific activity training Wear a respirator providing a minimum efficiency of 90% (APF 10) |
| Additional good practice advice beyond the REACH Chemical Safety Report | Workers involved in production, handling, sampling and transfer of materials are well-trained in these procedures as well as good industrial hygiene practices ----- |
| Process category(ies) | PROC4 - Use in batch and other process (synthesis) where opportunity for exposure arises |
| Covers concentrations up to | 100% |
| Exposure duration | < 8h hour(s) |
| Indoor/Outdoor use | Indoor |
| Assumes process temperature up to | <=40°C |
| Organisational measures to prevent /limit releases, dispersion and exposure | Provide extract ventilation to points where emissions occur Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimize exposures and to report any skin problems that may develop |
| Conditions and measures related to personal protection, hygiene and health evaluation | Use eye protection according to EN 166, designed to protect against liquid splashes Wear a respirator providing a minimum efficiency of 90% (APF 10) Wear chemically resistant gloves (tested to EN374) in combination with specific activity training |
| Additional good practice advice beyond the REACH Chemical Safety Report | Workers involved in production, handling, sampling and transfer of materials are well-trained in these procedures as well as good industrial hygiene practices ----- |
| Process category(ies) | PROC8a - Transfer of substance or preparation (charging/discharging) from/to |
| Covers concentrations up to | vessels/large containers at non dedicated facilities |
| Exposure duration | 100% |
| Indoor/Outdoor use | < 1 hour(s) |
| Assumes process temperature up to | Indoor |
| Organisational measures to prevent /limit releases, dispersion and exposure | <=40°C |
| Additional good practice advice beyond the REACH Chemical Safety Report | Drain or remove substance from equipment prior to break-in or maintenance Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimize exposures and to report any skin problems that may develop |
| Conditions and measures related to personal protection, hygiene and health evaluation | Use eye protection according to EN 166, designed to protect against liquid splashes Wear a respirator providing a minimum efficiency of 95% (APF 20) Wear chemically resistant gloves (tested to EN374) in combination with specific activity training |
| Additional good practice advice beyond the REACH Chemical Safety Report | Assumes a good basic standard of occupational hygiene is implemented ----- |
| Process category(ies) | PROC8b - Transfer of substance or preparation (charging/discharging) from/to |
| Covers concentrations up to | vessels/large containers at dedicated facilities |
| Exposure duration | 100% |
| Indoor/Outdoor use | < 8h hour(s) |
| Assumes process temperature up to | Indoor |
| Organisational measures to prevent /limit releases, dispersion and exposure | <=40°C |
| Additional good practice advice beyond the REACH Chemical Safety Report | Fill containers/cans at dedicated fill points supplied with local extract ventilation Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimize exposures and to report any skin problems that may develop |
| Conditions and measures related to personal protection, hygiene and health evaluation | Use eye protection according to EN 166, designed to protect against liquid splashes Wear chemically resistant gloves (tested to EN374) in combination with specific activity training |
| Additional good practice advice beyond the REACH Chemical Safety Report | Assumes a good basic standard of occupational hygiene is implemented ----- |

| | |
|---|---|
| Process category(ies) | PROC9 - Transfer of substance or preparation into small containers (dedicated filling line, including weighing) |
| Covers concentrations up to | 100% |
| Exposure duration | < 8h hour(s) |
| Indoor/Outdoor use | Indoor |
| Assumes process temperature up to | <=40°C |
| Organisational measures to prevent /limit releases, dispersion and exposure | Fill containers/cans at dedicated fill points supplied with local extract ventilation Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimize exposures and to report any skin problems that may develop |
| Conditions and measures related to personal protection, hygiene and health evaluation | Use eye protection according to EN 166, designed to protect against liquid splashes Wear chemically resistant gloves (tested to EN374) in combination with specific activity training Wear a respirator providing a minimum efficiency of 90% |
| Additional good practice advice beyond the REACH Chemical Safety Report | Assumes a good basic standard of occupational hygiene is implemented |

| | |
|---|---|
| Process category(ies) | PROC15 - Use as laboratory reagent |
| Covers concentrations up to | 100% |
| Exposure duration | < 8h hour(s) |
| Indoor/Outdoor use | Indoor |
| Assumes process temperature up to | <=40°C |
| Organisational measures to prevent /limit releases, dispersion and exposure | Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimize exposures and to report any skin problems that may develop |
| Conditions and measures related to personal protection, hygiene and health evaluation | Use eye protection according to EN 166, designed to protect against liquid splashes Wear chemically resistant gloves (tested to EN374) in combination with specific activity training |
| Additional good practice advice beyond the REACH Chemical Safety Report | Assumes a good basic standard of occupational hygiene is implemented |

Control of consumer exposure Not intended for consumer use

Section 3 - Exposure estimation

Environment

Environmental release category(ies)

ERC1 - Manufacture of substances

Predicted No Effect Concentration (PNEC) - See values below

| | | | |
|---|---------------|------------------------------|---------------|
| Fresh water | 0.31 mg/l | Marine water | 0.031 mg/l |
| Fresh water sediment | 2.57 mg/kg dw | Marine water sediment | 0.26 mg/kg dw |
| Water Intermittent | 0.27 mg/l | Soil (Agriculture) | 0.33 mg/kg dw |
| Microorganisms in sewage treatment | 25.9 mg/l | | |

| <u>Environment</u> | <u>Predicted exposure level</u> | <u>Risk characterization ratio (RCR)</u> |
|---------------------------------------|----------------------------------|--|
| Freshwater | 5.17 x 10 ⁻³ mg/l | <0.01 |
| Marine water | 9.3 x 10 ⁻³ mg/l | <0.01 |
| Freshwater sediment | 4.16 x 10 ⁻⁴ mg/kg dw | <0.01 |
| Marine sediment | 7.49 x 10 ⁻⁴ mg/kg dw | <0.01 |
| Soil | 1.26 x 10 ⁻⁴ mg/kg dw | <0.01 |
| Calculation method - EUSES 2.1 | | |

Remarks

No significant PEC values are indicated for the regional scale even under the conservative assumptions of the Tier 2 EUSES assessment. All derived PECs are below the relevant PNEC and so no further assessment or refinements are required.

Health**Derived No Effect Level (DNEL)** - See table for values

| <u>Route of exposure</u> | Acute effects (local) | Acute effects (systemic) | Chronic effects (local) | Chronic effects (systemic) |
|--------------------------|------------------------------|---------------------------------|--------------------------------|-----------------------------------|
| Oral | | | | |
| Dermal | | | | 12 mg/kg bw/d |
| Inhalation | 706 mg/m ³ | | 353 mg/m ³ | |

| Process category(ies) | Exposure route | Predicted exposure level | Risk characterization ratio (RCR) |
|---|-----------------------|---------------------------------|--|
| PROC1 - Use in closed process, no likelihood of exposure | Worker - inhalative | 0.01 ppm | <0.01 |
| | Worker - dermal | 0.07 mg/kg bw/day | < 0.01 |
| PROC2 - Use in closed, continuous process with occasional controlled exposure | Worker - inhalative | 50 ppm | 0.5 |
| | Worker - dermal | 0.27 mg/kg bw/day | < 0.01 |
| PROC3 - Use in closed batch process (synthesis or formulation) | Worker - inhalative | 10 ppm | 0.1 |
| | Worker - dermal | 1.37 mg/kg bw/day | < 0.01 |
| PROC4 - Use in batch and other process (synthesis) where opportunity for exposure arises | Worker - inhalative | 10 ppm | 0.1 |
| | Worker - dermal | 1.37 mg/kg bw/day | < 0.01 |
| PROC8a - Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non dedicated facilities | Worker - inhalative | 50 ppm | 0.5 |
| | Worker - dermal | 2.74 mg/kg bw/day | < 0.01 |
| PROC15 - Use as laboratory reagent | Worker - inhalative | 50 ppm | 0.5 |
| | Worker - dermal | 0.07 mg/kg bw/d | < 0.01 |

Calculation method Used ECETOC TRA model**Remarks**

Predicted exposures are not expected to exceed the DN(M)EL when the risk management measures/operational conditions outlined in section 2 are implemented

Section 4 - Guidance to check compliance with the exposure scenario

Used EUSES model

Used ECETOC TRA model

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>)

Predicted exposures are not expected to exceed the applicable exposure limits (given in section 8 of the SDS) when the operational conditions/risk management measures given in section 2 are implemented
ECHA guidance for downstream users

Annex to the Safety Data Sheet according to Regulation (EC) No 1907/2006 [REACH]

Dichloromethane - Exposure Scenarios

| | | |
|-------------------|--|--------------------|
| CAS No 75-09-2 | REACH registration number 01-2119480404-41-xxxx | EC No 200-838-9 |
|-------------------|--|--------------------|

Exposure scenario

Methylene chloride - ES2-M2 DCM

Section 1 - Identification of the use

| | |
|---|--|
| Main user group | Industrial use |
| Type | Worker |
| Processes, tasks, activities covered | Use as a Process Solvent / Extraction Medium (Industrial) |
| Sector(s) of use | SU3 - Industrial uses: Uses of substances as such or in preparations at industrial sites SU8 - Manufacture of bulk, large scale chemicals (including petroleum products) SU9 - Manufacture of fine chemicals |
| Process category(ies) | PROC1 - Use in closed process, no likelihood of exposure PROC2 - Use in closed, continuous process with occasional controlled exposure PROC3 - Use in closed batch process (synthesis or formulation) PROC4 - Use in batch and other process (synthesis) where opportunity for exposure arises PROC10 - Roller application or brushing PROC15 - Use as laboratory reagent |
| Environmental release category(ies) | ERC4 - Industrial use of processing aids in processes and products, not becoming part of articles |

Section 2 - Operational Conditions and Risk Management Measures

Product characteristics

| | |
|-----------------------------------|--------------------------------------|
| Physical State | Liquid |
| pH | No information available |
| Water Solubility | Partially miscible; 13.2 g/L @ 25 °C |
| Vapor Pressure | 325 mmHg @ 20°C |
| Volatility | High |
| Covers concentrations up to 100 % | |

Section 2.1 - Control of environmental exposure

Environmental release category(ies)
ERC4 - Industrial use of processing aids in processes and products, not becoming part of articles

Control of environmental exposure
Readily biodegradable

Regional use tonnage 2410 t/a
Annual amount per site 2410 t/a

Environmental factors not influenced by risk management

| | |
|--|------------|
| Emission days | 100 |
| Receiving water dilution (fresh or marine) | 18000 m3/d |

Other operational conditions of use affecting environmental exposure

| | |
|--|-------------------------------|
| Emission days | 100 (from ESVOC SPERC 1.1.v1) |
| Release fraction to air from process (initial release prior to RMM) | 0.669 |
| Release fraction to wastewater from process (initial release prior to RMM) | 0.00154 |
| Release fraction to soil from process (initial release prior to RMM) | 0.0 |

Technical onsite conditions and measures to reduce or limit discharges, air emissions

Technical onsite conditions and measures to reduce or limit discharges, air emissions

Negligible air emissions as process operates in a contained system.

Additional good practice advice beyond the REACH Chemical Safety Report

Bund storage facilities to prevent soil and water pollution in the event of spillage. Ensure all waste water is collected and treated via a WWTP.

Conditions and measures related to municipal sewage treatment plant

| | |
|---------|---|
| Remarks | Manufacturing plants will have on-site waste water treatment facilities and emission to the municipal STP will not occur. |
|---------|---|

Waste management

| | |
|-------|--|
| Air | No discharge. No air emission controls required. |
| Water | Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of 93.5% |

Conditions and measures related to external treatment of waste for disposal

| | |
|-------------------------|---|
| Disposal | Waste resulting from on-site RMM to be disposed as chemical waste |
| Waste treatment methods | Hazardous waste incineration |

Section 2.2 - Control of worker exposure**General information on risk management related to physicochemical hazard**

Keep equipment under negative pressure. Segregate work area and mark with appropriate signs in accordance with local/regional/national legislation.

General information on exposure estimation

Manufactured and processed at industrial sites in closed continuous processes with either no likelihood of exposure or with only occasional opportunity for exposure in controlled conditions e.g. during maintenance, sampling or discharge of the material.

Transfer of the substance is conducted at dedicated facilities using a closed-system with vapour return. Respiratory protection is not required except for certain critical activities where respiratory protective equipment is used, for example, cleaning tanks or reactors.

Control of worker exposure

| | |
|--|---|
| Process category(ies) | PROC1 - Use in closed process, no likelihood of exposure |
| Covers concentrations up to | 100% |
| Amounts used | >1000 t/y |
| Exposure duration | < 8h hour(s) |
| Use frequency | 100 days per year |
| Indoor/Outdoor use | Indoor |
| Assumes process temperature up to | <=40°C |
| Organisational measures to prevent /limit releases, dispersion and exposure | Handle substance within a closed system Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimize exposures and to report any skin problems that may develop |
| Technical conditions and measures to control dispersion from source towards the worker | Undertake operation under enclosed conditions |

| | |
|---|--|
| Conditions and measures related to personal protection, hygiene and health evaluation Additional good practice advice beyond the REACH Chemical Safety Report | Use eye protection according to EN 166, designed to protect against liquid splashes Wear chemically resistant gloves (tested to EN374) in combination with specific activity training Workers involved in production, handling, sampling and transfer of materials are well-trained in these procedures as well as good industrial hygiene practices ----- |
| Process category(ies) Covers concentrations up to Exposure duration Indoor/Outdoor use Assumes process temperature up to Organisational measures to prevent /limit releases, dispersion and exposure | PROC2 - Use in closed, continuous process with occasional controlled exposure 100% < 8h hour(s) Indoor <=40°C Handle substance within a closed system Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimize exposures and to report any skin problems that may develop |
| Conditions and measures related to personal protection, hygiene and health evaluation Additional good practice advice beyond the REACH Chemical Safety Report | Wear a respirator providing a minimum efficiency of 90% (APF 10) Use eye protection according to EN 166, designed to protect against liquid splashes Wear chemically resistant gloves (tested to EN374) in combination with specific activity training Workers involved in production, handling, sampling and transfer of materials are well-trained in these procedures as well as good industrial hygiene practices ----- |
| Process category(ies) Covers concentrations up to Exposure duration Indoor/Outdoor use Assumes process temperature up to Organisational measures to prevent /limit releases, dispersion and exposure | PROC3 - Use in closed batch process (synthesis or formulation) 100% < 8 hour(s) Indoor <=40°C Handle substance within a predominantly closed system provided with extract ventilation Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimize exposures and to report any skin problems that may develop |
| Conditions and measures related to personal protection, hygiene and health evaluation Additional good practice advice beyond the REACH Chemical Safety Report | Use eye protection according to EN 166, designed to protect against liquid splashes Wear chemically resistant gloves (tested to EN374) in combination with specific activity training Wear a respirator providing a minimum efficiency of 90% (APF 10) Workers involved in production, handling, sampling and transfer of materials are well-trained in these procedures as well as good industrial hygiene practices ----- |
| Process category(ies) Covers concentrations up to Exposure duration Indoor/Outdoor use Assumes process temperature up to Organisational measures to prevent /limit releases, dispersion and exposure | PROC4 - Use in batch and other process (synthesis) where opportunity for exposure arises 100% < 8h hour(s) Indoor <=40°C Provide extract ventilation to points where emissions occur Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimize exposures and to report any skin problems that may develop |
| Conditions and measures related to personal protection, hygiene and health evaluation Additional good practice advice beyond the REACH Chemical Safety Report | Use eye protection according to EN 166, designed to protect against liquid splashes Wear a respirator providing a minimum efficiency of 90% (APF 10) Wear chemically resistant gloves (tested to EN374) in combination with specific activity training Workers involved in production, handling, sampling and transfer of materials are well-trained in these procedures as well as good industrial hygiene practices ----- |
| Process category(ies) Covers concentrations up to Exposure duration Indoor/Outdoor use Assumes process temperature up to Organisational measures to prevent | PROC10 - Roller application or brushing 100% < 8h hour(s) Indoor <=40°C Provide extract ventilation to points where emissions occur Avoid direct skin contact with |

| | |
|--|---|
| /limit releases, dispersion and exposure | product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimize exposures and to report any skin problems that may develop |
| Technical conditions and measures to control dispersion from source towards the worker | Provide extract ventilation to points where emissions occur |
| Conditions and measures related to personal protection, hygiene and health evaluation | Use eye protection according to EN 166, designed to protect against liquid splashes Wear chemically resistant gloves (tested to EN374) in combination with specific activity training |
| Additional good practice advice beyond the REACH Chemical Safety Report | Assumes a good basic standard of occupational hygiene is implemented |
| ----- | |
| Process category(ies) | PROC15 - Use as laboratory reagent |
| Covers concentrations up to | 100% |
| Exposure duration | < 8h hour(s) |
| Indoor/Outdoor use | Indoor |
| Assumes process temperature up to | <=40°C |
| Organisational measures to prevent /limit releases, dispersion and exposure | Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimize exposures and to report any skin problems that may develop |
| Conditions and measures related to personal protection, hygiene and health evaluation | Use eye protection according to EN 166, designed to protect against liquid splashes Wear chemically resistant gloves (tested to EN374) in combination with specific activity training Wear a respirator providing a minimum efficiency of 90% |
| ----- | |
| Control of consumer exposure | Not intended for consumer use |

Section 3 - Exposure estimation

Environment

Environmental release category(ies)

ERC4 - Industrial use of processing aids in processes and products, not becoming part of articles

Predicted No Effect Concentration (PNEC) - See values below

| | | | |
|---|---------------|------------------------------|---------------|
| Fresh water | 0.31 mg/l | Marine water | 0.031 mg/l |
| Fresh water sediment | 2.57 mg/kg dw | Marine water sediment | 0.26 mg/kg dw |
| Water Intermittent | 0.27 mg/l | Soil (Agriculture) | 0.33 mg/kg dw |
| Microorganisms in sewage treatment | 25.9 mg/l | | |

| <u>Environment</u> | <u>Predicted exposure level</u> | <u>Risk characterization ratio (RCR)</u> |
|---------------------|----------------------------------|--|
| Freshwater | 5.17 x 10 ⁻³ mg/l | <0.01 |
| Marine water | 9.3 x 10 ⁻³ mg/l | <0.01 |
| Freshwater sediment | 4.16 x 10 ⁻⁴ mg/kg dw | <0.01 |
| Marine sediment | 7.49 x 10 ⁻⁴ mg/kg dw | <0.01 |
| Soil | 1.26 x 10 ⁻⁴ mg/kg dw | <0.01 |

Calculation method - EUSES 2.1

Remarks

No significant PEC values are indicated for the regional scale even under the conservative assumptions of the Tier 2 EUSES assessment. All derived PECs are below the relevant PNEC and so no further assessment or refinements are required.

Health

Derived No Effect Level (DNEL) - See table for values

| <u>Route of exposure</u> | <u>Acute effects (local)</u> | <u>Acute effects (systemic)</u> | <u>Chronic effects (local)</u> | <u>Chronic effects (systemic)</u> |
|--------------------------|------------------------------|---------------------------------|--------------------------------|-----------------------------------|
| Oral | | | | |

| | | | |
|-------------------|-----------------------|-----------------------|---------------|
| Dermal | | | 12 mg/kg bw/d |
| Inhalation | 706 mg/m ³ | 353 mg/m ³ | |

| Process category(ies) | Exposure route | Predicted exposure level | Risk characterization ratio (RCR) |
|--|---------------------|--------------------------|-----------------------------------|
| PROC1 - Use in closed process, no likelihood of exposure | Worker - inhalative | 0.01 ppm | <0.01 |
| | Worker - dermal | 0.07 mg/kg bw/day | < 0.01 |
| PROC2 - Use in closed, continuous process with occasional controlled exposure | Worker - inhalative | 50 ppm | 0.5 |
| | Worker - dermal | 0.27 mg/kg bw/day | < 0.01 |
| PROC3 - Use in closed batch process (synthesis or formulation) | Worker - inhalative | 10 ppm | 0.1 |
| | Worker - dermal | 1.37 mg/kg bw/day | < 0.01 |
| PROC4 - Use in batch and other process (synthesis) where opportunity for exposure arises | Worker - inhalative | 10 ppm | 0.1 |
| | Worker - dermal | 1.37 mg/kg bw/day | < 0.01 |
| PROC10 - Roller application or brushing | Worker - inhalative | 25 ppm | 0.25 |
| | Worker - dermal | 5.49 mg/kg bw/d | < 0.01 |
| PROC15 - Use as laboratory reagent | Worker - inhalative | 50 ppm | 0.5 |
| | Worker - dermal | 0.07 mg/kg bw/d | < 0.01 |

Calculation method Used ECETOC TRA model

Remarks

Predicted exposures are not expected to exceed the DN(M)EL when the risk management measures/operational conditions outlined in section 2 are implemented

Section 4 - Guidance to check compliance with the exposure scenario

Used EUSES model

Used ECETOC TRA model

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>)

Predicted exposures are not expected to exceed the applicable exposure limits (given in section 8 of the SDS) when the operational conditions/risk management measures given in section 2 are implemented
ECHA guidance for downstream users

Annex to the Safety Data Sheet according to Regulation (EC) No 1907/2006 [REACH]

Dichloromethane - Exposure Scenarios

| | | |
|-------------------|--|--------------------|
| CAS No 75-09-2 | REACH registration number 01-2119480404-41-xxxx | EC No 200-838-9 |
|-------------------|--|--------------------|

Exposure scenario

Methylene chloride - ES3-F1 DCM

Section 1 - Identification of the use

| | |
|---|---|
| Main user group | Industrial use |
| Type | Worker |
| Processes, tasks, activities covered | Use as a Process Solvent / Extraction Medium (Industrial) |
| Sector(s) of use | SU3 - Industrial uses: Uses of substances as such or in preparations at industrial sites SU10 - Formulation [mixing] of preparations and/or re-packaging (excluding alloys) |
| Process category(ies) | PROC3 - Use in closed batch process (synthesis or formulation) PROC4 - Use in batch and other process (synthesis) where opportunity for exposure arises PROC5 - Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact) PROC8a - Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non dedicated facilities PROC8b - Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities PROC9 - Transfer of substance or preparation into small containers (dedicated filling line, including weighing) PROC15 - Use as laboratory reagent |
| Environmental release category(ies) | ERC2 - Formulation of preparations (mixtures) |

Section 2 - Operational Conditions and Risk Management Measures

Product characteristics

| | |
|-----------------------------------|--------------------------------------|
| Physical State | Liquid |
| pH | No information available |
| Water Solubility | Partially miscible; 13.2 g/L @ 25 °C |
| Vapor Pressure | 325 mmHg @ 20°C |
| Volatility | High |
| Covers concentrations up to 100 % | |

Section 2.1 - Control of environmental exposure

Environmental release category(ies)
ERC2 - Formulation of preparations (mixtures)

Control of environmental exposure
Readily biodegradable
Regional use tonnage 2810 t/a
Annual amount per site 239 t/a

Environmental factors not influenced by risk management

| | |
|--|------------|
| Emission days | 300 |
| Receiving water dilution (fresh or marine) | 18000 m3/d |

Other operational conditions of use affecting environmental exposure

| | |
|--|-------------------------------|
| Emission days | 300 (from ESVOC SPERC 1.1.v1) |
| Release fraction to air from process (initial release prior to RMM) | 0.025 |
| Release fraction to wastewater from process (initial release prior to RMM) | 0.02 |
| Release fraction to soil from process (initial release prior to RMM) | 0.0 |

Technical onsite conditions and measures to reduce or limit discharges, air emissions

Technical onsite conditions and measures to reduce or limit discharges, air emissions

Negligible air emissions as process operates in a contained system.

Additional good practice advice beyond the REACH Chemical Safety Report

Bund storage facilities to prevent soil and water pollution in the event of spillage. Ensure all waste water is collected and treated via a WWTP.

Conditions and measures related to municipal sewage treatment plant

| | |
|---------|---|
| Remarks | Manufacturing plants will have on-site waste water treatment facilities and emission to the municipal STP will not occur. |
|---------|---|

Waste management

| | |
|-------|--|
| Air | No discharge. No air emission controls required. |
| Water | Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of 93.5% |

Conditions and measures related to external treatment of waste for disposal

| | |
|-------------------------|---|
| Disposal | Waste resulting from on-site RMM to be disposed as chemical waste |
| Waste treatment methods | Hazardous waste incineration |

Section 2.2 - Control of worker exposure**General information on risk management related to physicochemical hazard**

Keep equipment under negative pressure. Segregate work area and mark with appropriate signs in accordance with local/regional/national legislation.

General information on exposure estimation

Manufactured and processed at industrial sites in closed continuous processes with either no likelihood of exposure or with only occasional opportunity for exposure in controlled conditions e.g. during maintenance, sampling or discharge of the material.

Transfer of the substance is conducted at dedicated facilities using a closed-system with vapour return. Respiratory protection is not required except for certain critical activities where respiratory protective equipment is used, for example, cleaning tanks or reactors. Measured dermal exposure data are not available.

Control of worker exposure

| | |
|---|--|
| Process category(ies) | PROC3 - Use in closed batch process (synthesis or formulation) |
| Covers concentrations up to | 100% |
| Exposure duration | >4 hours (default) |
| Use frequency | 300 days per year |
| Indoor/Outdoor use | Indoor |
| Assumes process temperature up to | <=40°C |
| Organisational measures to prevent /limit releases, dispersion and exposure | Handle substance within a predominantly closed system provided with extract ventilation Use of closed transfers of liquids from storage to production equipment (e.g. metered piped or pumped additions) Sample via a closed loop or other system to avoid exposure |
| Conditions and measures related to personal protection, hygiene and health evaluation | Use eye protection according to EN 166, designed to protect against liquid splashes Wear chemically resistant gloves (tested to EN374) in combination with specific activity training Wear a respirator providing a minimum efficiency of 90% (APF 10) |
| Additional good practice advice beyond the REACH Chemical Safety Report | Workers involved in production, handling, sampling and transfer of materials are well-trained in these procedures as well as good industrial hygiene practices |

| | |
|--|---|
| Process category(ies) | PROC4 - Use in batch and other process (synthesis) where opportunity for exposure arises |
| Covers concentrations up to | 100% |
| Exposure duration | >4 hours (default) |
| Indoor/Outdoor use | Indoor |
| Assumes process temperature up to | <=40°C |
| Organisational measures to prevent /limit releases, dispersion and exposure | Provide extract ventilation to points where emissions occur Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimize exposures and to report any skin problems that may develop |
| Conditions and measures related to personal protection, hygiene and health evaluation | Use eye protection according to EN 166, designed to protect against liquid splashes Wear a respirator providing a minimum efficiency of 90% (APF 10) Wear chemically resistant gloves (tested to EN374) in combination with specific activity training |
| Additional good practice advice beyond the REACH Chemical Safety Report | Workers involved in production, handling, sampling and transfer of materials are well-trained in these procedures as well as good industrial hygiene practices ----- |
| Process category(ies) | PROC8a - Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non dedicated facilities |
| Covers concentrations up to | 100% |
| Exposure duration | >4 hours (default) |
| Indoor/Outdoor use | Indoor |
| Assumes process temperature up to | <=40°C |
| Organisational measures to prevent /limit releases, dispersion and exposure | Provide extract ventilation to points where emissions occur Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimize exposures and to report any skin problems that may develop |
| Conditions and measures related to personal protection, hygiene and health evaluation | Use eye protection according to EN 166, designed to protect against liquid splashes Wear a respirator providing a minimum efficiency of 95% (APF 20) Wear chemically resistant gloves (tested to EN374) in combination with specific activity training |
| Additional good practice advice beyond the REACH Chemical Safety Report | Workers involved in production, handling, sampling and transfer of materials are well-trained in these procedures as well as good industrial hygiene practices ----- |
| Process category(ies) | PROC8b - Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities |
| Covers concentrations up to | 100% |
| Exposure duration | >4 hours (default) |
| Indoor/Outdoor use | Indoor |
| Assumes process temperature up to | <=40°C |
| Organisational measures to prevent /limit releases, dispersion and exposure | Provide extract ventilation to points where emissions occur Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimize exposures and to report any skin problems that may develop |
| Process category(ies) | PROC9 - Transfer of substance or preparation into small containers (dedicated filling line, including weighing) |
| Covers concentrations up to | 100% |
| Exposure duration | >4 hours (default) |
| Indoor/Outdoor use | Indoor |
| Assumes process temperature up to | <=40°C |
| Organisational measures to prevent /limit releases, dispersion and exposure | Fill containers/cans at dedicated fill points supplied with local extract ventilation Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimize exposures and to report any skin problems that may develop |
| Technical conditions and measures to control dispersion from source towards the worker | Provide extract ventilation to points where emissions occur |
| Conditions and measures related to personal protection, hygiene and health evaluation | Use eye protection according to EN 166, designed to protect against liquid splashes Wear chemically resistant gloves (tested to EN374) in combination with specific activity training |

Additional good practice advice beyond the REACH Chemical Safety Report Workers involved in production, handling, sampling and transfer of materials are well-trained in these procedures as well as good industrial hygiene practices

| | |
|---|---|
| Process category(ies) | PROC15 - Use as laboratory reagent |
| Covers concentrations up to | 100% |
| Exposure duration | >4 hours (default) |
| Indoor/Outdoor use | Indoor |
| Assumes process temperature up to | <=40°C |
| Organisational measures to prevent /limit releases, dispersion and exposure | Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimize exposures and to report any skin problems that may develop |
| Conditions and measures related to personal protection, hygiene and health evaluation | Use eye protection according to EN 166, designed to protect against liquid splashes Wear chemically resistant gloves (tested to EN374) in combination with specific activity training Wear a respirator providing a minimum efficiency of 90% |

Control of consumer exposure Not intended for consumer use

Section 3 - Exposure estimation

Environment

Environmental release category(ies)

ERC2 - Formulation of preparations (mixtures)

Predicted No Effect Concentration (PNEC) - See values below

| | | | |
|---|---------------|------------------------------|---------------|
| Fresh water | 0.31 mg/l | Marine water | 0.031 mg/l |
| Fresh water sediment | 2.57 mg/kg dw | Marine water sediment | 0.26 mg/kg dw |
| Water Intermittent | 0.27 mg/l | Soil (Agriculture) | 0.33 mg/kg dw |
| Microorganisms in sewage treatment | 25.9 mg/l | | |

| <u>Environment</u> | <u>Predicted exposure level</u> | <u>Risk characterization ratio (RCR)</u> |
|----------------------------|----------------------------------|--|
| Freshwater | 5.17 x 10 ⁻³ mg/l | <0.01 |
| Marine water | 9.3 x 10 ⁻³ mg/l | <0.01 |
| Freshwater sediment | 4.16 x 10 ⁻⁴ mg/kg dw | <0.01 |
| Marine sediment | 7.49 x 10 ⁻⁴ mg/kg dw | <0.01 |
| Soil | 1.26 x 10 ⁻⁴ mg/kg dw | <0.01 |

Calculation method - EUSES 2.1

Remarks

No significant PEC values are indicated for the regional scale even under the conservative assumptions of the Tier 2 EUSES assessment. All derived PECs are below the relevant PNEC and so no further assessment or refinements are required.

Health

Derived No Effect Level (DNEL) - See table for values

| <u>Route of exposure</u> | <u>Acute effects (local)</u> | <u>Acute effects (systemic)</u> | <u>Chronic effects (local)</u> | <u>Chronic effects (systemic)</u> |
|--------------------------|------------------------------|---------------------------------|--------------------------------|-----------------------------------|
| Oral | | | | |
| Dermal | | | | |
| Inhalation | 706 mg/m ³ | | 353 mg/m ³ | 12 mg/kg bw/d |

| <u>Process category(ies)</u> | <u>Exposure route</u> | <u>Predicted exposure level</u> | <u>Risk characterization ratio (RCR)</u> |
|--|-----------------------|---------------------------------|--|
| PROC3 - Use in closed batch process (synthesis or formulation) | Worker - inhalative | 10 ppm | 0.1 |
| | Worker - dermal | 0.07 mg/kg bw/day | < 0.01 |
| PROC4 - Use in batch and other process | Worker - inhalative | 10 ppm | 0.1 |

(synthesis) where opportunity for exposure arises

| | | | |
|---|---------------------|-----------------------|--------|
| | Worker - dermal | 1.37 mg/kg bw/day | < 0.01 |
| PROC8a - Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non dedicated facilities | Worker - inhalative | 25 ppm | 0.3 |
| PROC8b - Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities | Worker - dermal | 2.74 mg/kg bw/day | < 0.01 |
| | Worker - inhalative | 4.5 mg/m ³ | 0.05 |
| PROC9 - Transfer of substance or preparation into small containers (dedicated filling line, including weighing) | Worker - dermal | 1.37 mg/kg bw/day | < 0.01 |
| | Worker - inhalative | 20 mg/m ³ | 0.2 |
| PROC15 - Use as laboratory reagent | Worker - dermal | 1.37 mg/kg bw/day | < 0.01 |
| | Worker - inhalative | 50 ppm | 0.5 |
| | Worker - dermal | 0.07 mg/kg bw/d | < 0.01 |

Calculation method Used ECETOC TRA model

Remarks

Predicted exposures are not expected to exceed the DN(M)EL when the risk management measures/operational conditions outlined in section 2 are implemented

Section 4 - Guidance to check compliance with the exposure scenario

Used EUSES model

Used ECETOC TRA model

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>)

Predicted exposures are not expected to exceed the applicable exposure limits (given in section 8 of the SDS) when the operational conditions/risk management measures given in section 2 are implemented

ECHA guidance for downstream users

Annex to the Safety Data Sheet according to Regulation (EC) No 1907/2006 [REACH]

Dichloromethane - Exposure Scenarios

| | | |
|-------------------|--|--------------------|
| CAS No 75-09-2 | REACH registration number 01-2119480404-41-xxxx | EC No 200-838-9 |
|-------------------|--|--------------------|

Exposure scenario

Methylene chloride - ES4-L1 DCM

Section 1 - Identification of the use

| | |
|---|--|
| Main user group | Industrial use |
| Type | Worker |
| Processes, tasks, activities covered | Laboratory use (Professional) |
| Sector(s) of use | SU3 - Industrial uses: Uses of substances as such or in preparations at industrial sites SU10 - Formulation [mixing] of preparations and/or re-packaging (excluding alloys) |
| Process category(ies) | PROC10 - Roller application or brushing PROC15 - Use as laboratory reagent |
| Environmental release category(ies) | ERC8a - Wide dispersive indoor use of processing aids in open systems |

Section 2 - Operational Conditions and Risk Management Measures

Product characteristics

| | |
|-----------------------------------|--------------------------------------|
| Physical State | Liquid |
| pH | No information available |
| Water Solubility | Partially miscible; 13.2 g/L @ 25 °C |
| Vapor Pressure | 325 mmHg @ 20°C |
| Volatility | High |
| Covers concentrations up to 100 % | |

Section 2.1 - Control of environmental exposure

Environmental release category(ies)
ERC8a - Wide dispersive indoor use of processing aids in open systems

Control of environmental exposure

Readily biodegradable
Regional use tonnage 257 t/a
Annual amount per site 257 t/a

Environmental factors not influenced by risk management

| | |
|--|------------|
| Emission days | 300 |
| Receiving water dilution (fresh or marine) | 18000 m3/d |

Other operational conditions of use affecting environmental exposure

| | |
|---|-------------------------------|
| Emission days | 300 (from ESVOC SPERC 1.1.v1) |
| Release fraction to air from process (initial release prior to RMM) | 0.5 |

Release fraction to wastewater from process (initial release prior to RMM) 0.5
 Release fraction to soil from process (initial release prior to RMM) 0.0

Technical onsite conditions and measures to reduce or limit discharges, air emissions

Technical onsite conditions and measures to reduce or limit discharges, air emissions

Negligible air emissions as process operates in a contained system.

Additional good practice advice beyond the REACH Chemical Safety Report

Bund storage facilities to prevent soil and water pollution in the event of spillage. Ensure all waste water is collected and treated via a WWTP.

Conditions and measures related to municipal sewage treatment plant

Remarks Manufacturing plants will have on-site waste water treatment facilities and emission to the municipal STP will not occur.

Waste management

Air No discharge. No air emission controls required.
 Water Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of 93.5%

Conditions and measures related to external treatment of waste for disposal

Disposal Waste resulting from on-site RMM to be disposed as chemical waste
 Waste treatment methods Hazardous waste incineration

Section 2.2 - Control of worker exposure

General information on risk management related to physicochemical hazard

Keep equipment under negative pressure. Segregate work area and mark with appropriate signs in accordance with local/regional/national legislation.

General information on exposure estimation

Manufactured and processed at industrial sites in closed continuous processes with either no likelihood of exposure or with only occasional opportunity for exposure in controlled conditions e.g. during maintenance, sampling or discharge of the material.

Transfer of the substance is conducted at dedicated facilities using a closed-system with vapour return. Respiratory protection is not required except for certain critical activities where respiratory protective equipment is used, for example, cleaning tanks or reactors. Measured dermal exposure data are not available.

Control of worker exposure

Process category(ies) PROC15 - Use as laboratory reagent
 Covers concentrations up to 100%
 Exposure duration >4 hours (default)
 Use frequency 300 days per year
 Indoor/Outdoor use Indoor
 Assumes process temperature up to <=40°C
 Organisational measures to prevent /limit releases, dispersion and exposure Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimize exposures and to report any skin problems that may develop
 Conditions and measures related to personal protection, hygiene and health evaluation Use eye protection according to EN 166, designed to protect against liquid splashes Wear chemically resistant gloves (tested to EN374) in combination with specific activity training
 Wear a respirator providing a minimum efficiency of 90%

Process category(ies) PROC10 - Roller application or brushing
 Covers concentrations up to 100%
 Exposure duration Avoid carrying out activities involving exposure for more than 4 hours
 Use frequency 300 days per year
 Indoor/Outdoor use Indoor
 Assumes process temperature up to <=40°C
 Organisational measures to prevent /limit releases, dispersion and exposure Provide extract ventilation to points where emissions occur Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur.

Wash off any skin contamination immediately. Provide basic employee training to prevent / minimize exposures and to report any skin problems that may develop

Control of consumer exposure Not intended for consumer use

Section 3 - Exposure estimation

Environment

Environmental release category(ies)

ERC8a - Wide dispersive indoor use of processing aids in open systems

Predicted No Effect Concentration (PNEC) - See values below

| | | | |
|---|---------------|------------------------------|---------------|
| Fresh water | 0.31 mg/l | Marine water | 0.031 mg/l |
| Fresh water sediment | 2.57 mg/kg dw | Marine water sediment | 0.26 mg/kg dw |
| Water Intermittent | 0.27 mg/l | Soil (Agriculture) | 0.33 mg/kg dw |
| Microorganisms in sewage treatment | 25.9 mg/l | | |

| <u>Environment</u> | <u>Predicted exposure level</u> | <u>Risk characterization ratio (RCR)</u> |
|----------------------------|---------------------------------|--|
| Freshwater | 5.17×10^{-3} mg/l | <0.01 |
| Marine water | 9.3×10^{-3} mg/l | <0.01 |
| Freshwater sediment | 4.16×10^{-4} mg/kg dw | <0.01 |
| Marine sediment | 7.49×10^{-4} mg/kg dw | <0.01 |
| Soil | 1.26×10^{-4} mg/kg dw | <0.01 |

Calculation method - EUSES 2.1

Remarks

No significant PEC values are indicated for the regional scale even under the conservative assumptions of the Tier 2 EUSES assessment. All derived PECs are below the relevant PNEC and so no further assessment or refinements are required.

Health

Derived No Effect Level (DNEL) - See table for values

| <u>Route of exposure</u> | <u>Acute effects (local)</u> | <u>Acute effects (systemic)</u> | <u>Chronic effects (local)</u> | <u>Chronic effects (systemic)</u> |
|------------------------------|------------------------------|---------------------------------|--------------------------------|-----------------------------------|
| Oral Dermal Inhalation | | | | 12 mg/kg bw/d |
| | 706 mg/m ³ | | 353 mg/m ³ | |

| <u>Process category(ies)</u> | <u>Exposure route</u> | <u>Predicted exposure level</u> | <u>Risk characterization ratio (RCR)</u> |
|---|-----------------------|---------------------------------|--|
| PROC10 - Roller application or brushing | Worker - inhalative | 60 ppm | 0.6 |
| | Worker - dermal | 5.49 mg/kg bw/d | < 0.01 |
| PROC15 - Use as laboratory reagent | Worker - inhalative | 50 ppm | 0.5 |
| | Worker - dermal | 0.07 mg/kg bw/d | < 0.01 |

Calculation method Used ECETOC TRA model

Remarks

Predicted exposures are not expected to exceed the DN(M)EL when the risk management measures/operational conditions outlined in section 2 are implemented

Section 4 - Guidance to check compliance with the exposure scenario

Used EUSES model

Used ECETOC TRA model

Further details on scaling and control technologies are provided in SpERC factsheet

(<http://cefic.org/en/reach-for-industries-libraries.html>)

Predicted exposures are not expected to exceed the applicable exposure limits (given in section 8 of the SDS) when the operational conditions/risk management measures given in section 2 are implemented
ECHA guidance for downstream users